

Solid State Power Amplifier 100-2000 MHz, 50 Watts

Model BME1829-50 with Low/ High Band

Overview

Model BME1829-50W is a Class A/AB CW GaN linear amplifier, which operates over the full 100 to 2000 MHz bandwidth with a built in TTL controlled Low/High Band Switch. In the Low Band Mode, the SSPA supplies >2W from 100-799MHz, and in the High Band mode the SSPA supplies > 50W from 800-2000MHz, both modes provide rated power into a 3:1 load VSWR when driven with a -10dBm RF signal. The amplifier also features a Dual Direction Coupler on the output and features thermal shut-down protection above 95C baseplate temperature. The SSPA is designed to meet MIL STD 810F Shock and Vibration as well as can operate up to 25K feet with 95% humidity N/C. The assembly is 5.5" x 4.5" x 1.6" and weighs 1.9 lbs. Unit must be mounted to a proper heatsink (not supplied).



Features

- GaN Technology
- Wide Band Operation
- > 2W CW from 100-500MHz
- >50W CW from 800-2000MHz
- TTL Hot Switchable Band Control
- Dual Directional Coupler
- Compact & Light Weight
- Military Environment

Specifications

Electrical

- Frequency Range: 100 to 2000 MHz
- Low Band Mode: 100-799MHz
- High Band Mode: 800-2000MHz
- RF Input Power: -10 dBm + 0dBm @ +25°C
- RF Output Rated Power: >2 Watts (Low Band Mode)
- RF Output Rated Power: >50 Watts (High Band Mode)
- Small Signal Gain Flatness: < + 3.0 dB
- RF Input Overdrive: +5 dBm
- Input VSWR: < 2:1
- Harmonic Rejection (High Band): <-12 dBc
- Spurious Signals: <-55 dBc
- Class of Operation: A/AB Linear
- DC Input @ 47dBm: +28 VDC + 0.5V @ 7A typical
- PA Enable: <5 μs
- Load VSWR: 3:1 Full Power; Infinite 30 sec
- Noise Figure < 12dB
- Fwd/Rev DDC Ports 50dB+2 with 20dB Directivity

- Blanking Speed < 5usec
- Blanked Noise Level -150dBc/Hz
- Band Switch Speed(5V TTL): <10msec

Environmental

- Temperature
- Operating: -40°C to +85° Base Plate
 - Storage: -40°C to +95°C
 - Thermal shutdown: +95°C + 5°C
- Altitude
- Operating: 30,000 feet
 - Non-Operating: 40,000 feet
- Shock: MIL-STD-810F Method 516.5
- Vibration: MIL-STD-810F Method 514.8
- Humidity: 95% without condensation
- Cooling: Conduction cooled

Physical

- Size: 5.5" x 4.5" x 1.6"
- Weight: 1.9 lbs.

Power Systems Technology (PST)

105 Baylis Road
Melville, NY 11747
T: 631-777-8900

417 Boston St.
Topsfield, MA 01983
T: 978-887-5754



www.Stellantsystems.com



For more information, contact

Sales@Stellantsystems.com