

20 to 1000 MHz, 25 Watts MODEL BME2719-25

Features:

- Solid State Design
- Wide Band Operation
- Compact & Light Weight
- Military Environment



PERFORMANCE SPECIFICATIONS

ELECTRICAL

- Frequency Range: 20 to 1000 MHz
- RF Output Power: 25 Watts
- RF Gain: 46 dB \pm 1.5 dB
- RF Input Overdrive: +10 dB
- Input VSWR: 2:1 maximum
- Harmonic Rejection: -25 dBc
- Spurious Signals: -60 dBc
- Class of Operation: AB Linear
- DC Input: +28 VDC
- DC Current: 3.8 A typical
- PA Enable: 20 μ s
- Load VSWR: Infinite

ENVIRONMENTAL

- Temperature:
 - Operating: -40°C to +80° Mounting Base Temperature
 - Storage: -40°C to +85°C
- Altitude:
 - Operating: 30,000 feet
 - Non-Operating: 40,000 feet
- Shock: MIL-STD-810F Method 516.5
- Vibration: MIL-STD-810F Method 514.5
- Humidity: 95% without condensation
- Cooling: Baseplate

PHYSICAL

- Size: 6.4" x 3.4" x 1.06"
- Weight: 1 lb. typical

Model BM2719-25 is a Class AB linear amplifier, which operates over the full 20 to 1000 MHz frequency range with output power of 25 watts. The amplifier is very compact (6.4" x 3.4" x 1.06"), and weighs only 1 pound.

Contact your local Comtech PST representative, or visit us at www.comtechpst.com.

E-mail Address: sales@comtechpst.com

SPECIFICATIONS ARE SUBJECT TO CHANGE
Certified for Public Release (CPST, PRM-09-04)