
	Cage Code:	Title:	Date:	Rev:	Model no:
	02WL0	<b>PRODUCT DATA</b> <b>(subject to change)</b>	06/27/06	None	<b>M20-041</b>

**This document describes the performance of a high power 1P2T switch. This is a cold-switched design i.e.; switched while RF is off. Proper bias per section 11 must be applied before operating this switch.**

ITEM NO	CHARACTERISTIC	CONDITIONS	MIN	MAX	UNITS	COMMENTS
1	POWER SPECIFICATION	IN BAND				
1.1	FREQUENCY		40	260	MHz	
1.2	PEAK POWER			125	WATTS	
1.3	PULSE WIDTH		50	1000	nS	
1.4	DUTY			15	%	
1.5	AVG POWER			30	WATTS	
1.6	CW POWER			10	WATTS	
2	POWER SPECIFICATIONS	GUARD BAND				
2.1	FREQUENCY		260	400	MHz	
2.2	PEAK POWER			10	WATTS	
2.3	PULSE WIDTH		50	1000	nS	
2.4	DUTY			15	%	
2.5	CW POWER			10	WATTS	
3	POWER SPECIFICATIONS	OUT OF BAND				
3.1	FREQUENCY		>400		MHz	
3.2	PEAK POWER			30	dBm	
3.3	PULSE WIDTH			CW	μS	
3.4	DUTY			CW	%	
3.5	CW POWER			30	dBm	
4	OPERATING FREQUENCY		60	240	MHz	
5	INSERTION LOSS			0.7	dB	
6	ISOLATION					
6.1	I/O		40		dB	
7	PHASE					
7.1	MATCHING/TRACKING					NOT SPECIFIED
8	VSWR					
8.1	PORT SELECTED			1.6:1		
8.2	PORT NOT SELECTED			2:1		
8.2.1	OFF TERMINATION POWER	PEAK POWER AVERAGE POWER		20 5	WATTS	
8.3	LOAD			2.0:1		
8.4	SOURCE			2.0:1		

Federal Cage Code 02WLO

	Cage Code:	Title:	Date:	Rev:	Model no:
	02WLO	<b>PRODUCT DATA</b> <b>(subject to change)</b>	06/27/06	None	<b>M20-041</b>

ITEM NO	CHARACTERISTIC	CONDITIONS	MIN	MAX	UNITS	COMMENTS
9	HARMONICS & SPURS					
9.1	INTERNALLY GENERATED		40		dBc	
10	SWITCHING					
10.1	SPEED	TO 0.50DB I.L.		150	nS	
10.2	SWITCHING RATE			150	KHz	
10.3	VIDEO LEAKAGE			5	Vpp	Across 50 Ohms
10.4	COMMAND LOGIC	RS-422				120 Ohm Balanced logic
10.5	LOGIC TABLE					See Dwg 3414 below
11	D.C. POWER					
11.1	POSITIVE BIAS VOLTAGE 1		4.80	5.20	VDC	
11.3	NEGATIVE BIAS VOLTAGE		-26	-32	VDC	
11.4	POSITIVE BIAS CURRENT 1			300	mA	
11.4	NEGATIVE BIAS CURRENT			100	mA	
11.5	NOTE : Voltage Protection – This unit does not have over-voltage or reverse polarity protection on any bias port.					
12	CONNECTORS					
12.1	RF					SMAF
12.3	DC					Solder Pins
13	MECHANICAL					
13.1	WEIGHT			4	Oz	
13.2	OUTLINE					See Dwg 3414 below
14	ENVIRONMENTAL					
14.1	OPERATING TEMPERATURE		0	+50	°C	
14.2	STORAGE TEMPERATURE		-20	+55	°C	
14.3	VIBRATION LEVEL					GROUND TRANSPORT



Cage Code:  
**02WLO**

Title:  
**PRODUCT DATA**  
**(subject to change)**

Date:  
**06/27/06**

Rev:  
**None**

Model no:  
**M20-041**

